



FCamSolo™

Detection	
Detection Distance	55m (4mm lens) 100m (6mm lens)
Fire Detection	Hybrid video flame detection. Combined IR & visual analytics onboard
Detection Time	< 15 Seconds
Environment	
Rating	IP60
Working Humidity	< 96%
High & Low Temp	-10°C to +70°C
Viewing Angle	
Horizontal	65° (4mm lens) 46° (6mm lens)
Vertical	36° (4mm lens) 25° (6mm lens)
Video	
Format	RTSP
Main Video Stream	1920p x 1080p @ 25fps
Sub Video Stream	320p x 240p @ 5fps
Bandwidth	Max 8 Mbps
VOE	H.264 1080p
Net Protocol	QLS, RTSP, TELNET, FTP
Video Encoder	H.264
Image Sensor	1/3" Low Lux

Video	
Digital Noise Reduction	3D DNR
Video Stream Protocol	RTSP
Dimensions & Weight	
Diameter	115mm
Height	140mm
Weight	0.6 Kg
Power	
Power Supply	DC 12v 1A
Power Capacity	4w (Max 12w)
Quiescent Current	<200mA
Communication	
Communication Interface	RJ45
Analytics	
External Analytics Capable	Yes
Part Code	
Ciqurix order code	FC-S-104 (4mm) FC-S-106 (6mm)

